

Capacity	Accuracy	Part number
100Kg	C3	H6B-C3-100Kg-3B6
150Kg	C3	H6B-C3-150Kg-3B6
200Kg	C3	H6B-C3-200Kg-3B6
250Kg	C3	H6B-C3-250Kg-3B6
300Kg	C3	H6B-C3-300Kg-3B6
350Kg	C3	H6B-C3-350Kg-3B6
500Kg	C3	H6B-C3-500Kg-3B6
1500Kg	C3	H6B-C3-1500Kg-3B6



Specifications			
Accuracy Class	C3	Temperature effect on span (%FS/10 C)	0.014
Rated output (mV/V)	2.5±0.1	Temperature effect on zero (%FS/10 C)	0.017
Combined error (%FS)	0.02	Temperature, Compensated (C)	-10~+40
Non-linearity (%FS)	0.017	Temperature, Operating (C)	-35~+65
Non-repeatability (%FS)	0.01	Excitation, Recommended (V)	5-12(DC)
Creep (%FS/30min)	0.02	Excitation, Max. (V)	18(DC)
Input Resistance (Ω)	383±3	Safe Overload (%FS)	150
Output Resistance (Ω)	350±3	Ultimate Overload (%FS)	300
Insulation Resistance (MΩ)	≥5000(50VDC)	Protection Class	IP 67
Zero Balance (%FS)	1.5	Cable Length (m)	3
Off center load error (% , per OIML R76)	0.02	Cable spec	6-wire shielded cable

**Connections** Red Input (+) Yellow Input (-) Blue Output(+) White Output(-)  
Brown Sense(+) Black Sense(-) Transparence (shield)

